

CODE NUMBER

33440002

DESCRIPTION

0.5 lpf, Polished Chrome Finish, Fixture Connection , Single Flush, Battery with Hardwired Option, Infrared, Front Accessible Wall Box, Concealed Sensor Urinal Flush Valve Wall Plate.

DETAILS

- Flush Volume: 0.5 Lpf
- Finish: Polished Chrome (CP)
- Power Type: Battery with Hardwired Option
- Battery Life: 5 years
- Fixture Type: Urinal
- Wall Box: Front Accessible

FEATURES

- Chrome-plated, corrosion-resistant and vandal-resistant metal wall plate
- Compatible for use with Sloan SGV-7900 Sensor Urinal Flush Valve
- Operates from 0.7 bar to 5.5 bar water pressure (10 psi to 80 psi)
- Sloan water resistant electronic PCB
- Battery (DC) or Hardwired with Battery backup (AC/DC) power options
- Adjustable sensor range - 550 mm to 750 mm (sensing distance 625 mm as default)
- Arm delay time - 8 Sec
- Wait delay time - 1 sec
- Includes four (4) AA size batteries
- Sensor urinal flush valve (SGV-7900) sold separately



ELECTRICAL SPECIFICATIONS

- Arming Delay: 8 seconds
- Battery Life: 5 years
- Control Circuit: 6 VDC InputSolid State
- Sensor Range: 22" - 30" (559 - 762mm)
- Solenoid Operator: 6 VAC

VALVE OPERATING PRESSURE (FLOWING)

10-80 PSI (69-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- [Concealed Sensor Urinal Flush Wall Plate Installation Instructions](#)

NOTES

All information contained within this document subject to change without notice.

[Find a compatible urinal](#) for this flush valve wall plate.